

	Material thickness (mm)	Clean and smooth ground surface Air gap < 0.1 mm		Corroded and hot-rolled surface Air gap 0.1-0.3 mm		Irregular and rough surface Air gap 0.3-0.5 mm		Very rough surface Air gap > 0.5 mm
		Max. dimensions L×W (mm)	Weight limit (kg)	Max. dimensions L×W (mm)	Weight limit (kg)	Max. dimensions L×W (mm)	Weight limit (kg)	
<b>BMP 1800</b>	≥50	2000 x 2000	1800	1700 x 1500	1030	1500 x 1500	930	Ask your supplier for advice
	38	1900 x 1900	1130	1800 x 1500	930	1800 x 1500	850	
	25	2100 x 2100	1020	2100 x 1800	840	2100 x 1800	760	
	19	2400 x 2100	800	2100 x 1800	660	2100 x 1800	590	
	13	2400 x 2100	570	2100 x 2100	470	2100 x 1800	420	
	10	2100 x 2100	390	2100 x 1800	310	2100 x 1500	270	
	6	2000 x 2000	250	2000 x 1500	200	1800 x 1500	150	
<b>BMP 3600</b>	≥70	-	3600	-	3400	-	3200	
	40	2700 x 2700	2275	2400 x 2400	2440	2400 x 2100	2320	
	30	3000 x 3000	1730	2700 x 2700	1570	2700 x 2400	1420	
	20	3000 x 3000	1250	2700 x 2700	1140	2700 x 2400	1050	
	15	3000 x 3000	920	2700 x 2700	840	2700 x 2400	780	
	10	2700 x 2700	610	2700 x 2400	580	2400 x 2400	520	
	6	3000 x 2700	370	2700 x 2400	350	2700 x 2400	320	

		Diameter (mm)		Weight limit (kg)		Max. length (mm)
		BMP 1800	BMP 3600	BMP 1800	BMP 3600	
BMP 1800/3600	Load type	Ø 40 - Ø 440	Ø 45 - Ø 500	1130	2260	6000