

	Material thickness (mm)	Clean and smooth ground surface Air gap < 0.1 mm		Corroded and hot-rolled surface Air gap 0.1–0.3 mm		Irregular and rough surface Air gap 0.3-0.5 mm		Very rough surface Air gap > 0.5 mm
		Max. dimensions L×W (mm)	Weight limit (kg)	Max. dimensions L×W (mm)	Weight limit (kg)	Max. dimensions L×W (mm)	Weight limit (kg)	
BM 1350	≥ 38	2130 x 2130	1360	1900 x 1900	1160	1700 x 1700	900	Ask your supplier for advice
	25	2130 x 2130	950	1830 x 1830	890	1830 x 1830	770	
	19	2130 x 2130	660	1830 x 1830	580	1830 x 1830	500	
	13	2130 x 2130	370	1830 x 1830	340	1520 x 1520	260	
	10	1830 x 1520	180	1520 x 1520	160	1520 x 1520	150	
	6	1220 x 1220	90	1220 x 1220	86	1220 x 1220	80	
BM 2500	≥ 50	2400 x 2400	2500	2400 x 2100	2100	2100 x 2100	1750	
	38	2400 x 2400	1850	2400 x 2100	1620	2100 x 2100	1350	
	25	2400 x 2400	1200	2400 x 2100	1130	2100 x 2100	950	
	19	2400 x 2100	800	2100 x 2100	700	2100 x 1800	610	
	13	1800 x 1800	370	1800 x 1800	360	1800 x 1800	330	
	10	1800 x 1500	250	1800 x 1500	200	1800 x 1500	180	
BM 5000	6	1500 x 1200	110	1500 x 1200	100	1500 x 1200	90	
	≥ 50	3600 x 3300	5000	3300 x 3300	4200	3000 x 2700	3500	
	38	3300 x 3300	3700	3300 x 3000	3240	3000 x 2700	2700	
	25	3300 x 3300	2400	3300 x 3000	2260	3000 x 2700	1900	
	19	3000 x 2700	1600	3000 x 2700	1400	2700 x 2700	1220	
	13	2700 x 2400	740	2700 x 2400	720	2400 x 2400	660	
	10	2100 x 2100	500	2100 x 2100	400	2100 x 2100	360	
BM 3600	6	1800 x 1800	220	1800 x 1800	200	1800 x 1800	180	
	≥ 25	6000 x 3000	3600	6000 x 2700	3270	4500 x 3000	2730	
	19	6600 x 2400	2430	6000 x 2400	2230	4500 x 2400	1960	
	13	5100 x 2400	1250	4800 x 2400	1180	4500 x 2400	1090	
	10	3900 x 2400	720	3600 x 2400	660	3300 x 2400	610	
	6	3600 x 1800	340	3300 x 1800	300	3300 x 1500	270	
3	2400 x 1800	110	2100 x 1800	100	1800 x 1800	90		