

Maxgrip



**MONOBLOCK
PROTECTED**

- 100% WATERTIGHT
- 30% LONGER LIFE
- 15% LESS WEIGHT



When to choose permanent chuck Maxgrip:

Permanent circular magnetic chuck Maxgrip stands out for its high clamping force and versatility in use. The combination of solid top plate with relatively fine parallel pole arrangement and possibility to continuously control the clamping force means very easy centering of the workpieces during turning or grinding operations.

APPLICATION	TECHNOLOGY	DIAMETER	HOLDING FORCE	POLES
				
Circular grinding	Permanent	from 200 mm	160 N/cm ²	Parallel

Important parameters:

Application:	Circular grinding, turning
Technology:	Permanent
Min. workpiece diameter:	40 x 8 mm
Regrinding limit:	10 mm
Poles:	T15/11 + 4 mm - steel/epoxy

Use:

+ clamping of workpieces during turning and circular grinding

Model	D (mm)	H (mm)	G (mm)	D1 (mm)	Weight (kg)
MAXGRIP155	155	57	5	50	7
MAXGRIP200	200	57	5	60	15
MAXGRIP250	250	57	5	80	22
MAXGRIP300	300	57	6	150	32
MAXGRIP350	350	57	6	170	43
MAXGRIP400	400	57	8	200	56

